



# Adinath

Create, Enhance & Sustain

## C-66800:HIGH TENSILE BRASS

### Specification Sheet

#### DESCRIPTION

Manganese Bronze comes from a family of High strength copper based alloys which includes Manganese as an alloying agent with additions of Iron, Aluminium, Zinc, Lead and sometimes Nickel or Silicon. It has exceptionally high strength as compared to normal brass and therefore commonly known as High Tensile Brass, High Tensile Manganese Bronze, High Strength Brass or Manganese Aluminium Bronze.



#### CHEMICAL COMPOSITION

Element	Cu	Al	Fe	Ni	Mn	Zn	Pb	Sn	Si
Min (%)	60.00	-	-	-	2.00	Balance	-	-	0.50
Max (%)	63.00	0.25	0.35	0.25	3.50		0.50	0.30	1.50

Note: Ni includes Co; Cu+ named elements >= 99.5%; Unless otherwise noted, single values represent maximums.

#### SHAPE



**SOLID ROUND BARS**  
**Size Range :**  
 Dia 10 mm up to 120 mm.



**SOLID HEX BARS**  
**Size Range :**  
 A/F 10 mm up to 100 mm.



**SOLID SQUARE BARS**  
**Size Range :**  
 A/F 10 mm up to 90 mm.



**SOLID RECTANGLE BARS**  
**Size Range :**  
 A/F 10 x 12 mm up to 100 x 50 mm.



**HOLLOW BARS**  
**Outer Diameter :** In Round, Hex & Square  
**Size Range :** 30 mm up to 120 mm.  
**Inner Diameter :** Round  
**Size Range :** 20 mm up to 80 mm.



**PROFILES & SECTIONS**  
 As per Customers' Drawing



**BAR LENGTH**  
**Length :** Up to 4 Meters.  
**Delivery Condition :** As Extruded or Cold Drawn.



**CROSS KNURLING**



Straight Knurling & Cross Knurling will be available upon shape & size Feasibility of Brass Rod

# C-66800:HIGH TENSILE BRASS



## MECHANICAL PROPERTIES

Round (Dia)				
Range (mm)	UTS Min (N/MM <sup>2</sup> )	PS Min (N/MM <sup>2</sup> )	Elongation Min (%)	Hardness (HRB)
Over 25 to 50 Inclusive	440	180	20	-
Over 50 to 75 Inclusive	440	180	20	-
Hex (A/F)				
Range (mm)	UTS Min (N/MM <sup>2</sup> )	PS Min (N/MM <sup>2</sup> )	Elongation Min (%)	Hardness (HRB)
Over 25 to 50 Inclusive	440	180	20	-
Over 50 to 75 Inclusive	440	180	25	-
Square (A/F)				
Range (mm)	UTS Min (N/MM <sup>2</sup> )	PS Min (N/MM <sup>2</sup> )	Elongation Min (%)	Hardness (HRB)
Over 25 to 50 Inclusive	440	180	20	-
Over 50 to 75 Inclusive	440	180	20	-
Rectangle				
Range (mm)	UTS Min (N/MM <sup>2</sup> )	PS Min (N/MM <sup>2</sup> )	Elongation Min (%)	Hardness (HRB)
Thickness	440	180	20	-
Width				
	Over 12 to 50 Inclusive			
	Over 4 to 50 Inclusive			

## PACKING



-  PVC Pipe Packing for Small Diameter Rods.
-  Hessian Cloth Packing.
-  Wooden Box Packing as per Customer requirements.

## FABRICATION PROPERTIES

Soldering	Brazing	Machinability Rating
Excellent	Good	100

# C-66800:HIGH TENSILE BRASS



## TYPICAL USES

Product Category	Product
Industrial	Bearings, Bushings, Cams, Connecting Rods, Drive Shafts, Gears, Idler Pins, Piston Heads, Sealing Rings, Sleeve Bearings, Spindles, Thrust Bearings, Valve Seats.
Marine	Hardware, High Strength, Pump Parts.

## VALUE ADDED SERVICES

AEPL manufactures and supplies Copper Alloys Extruded Bars to Domestic as well as International Markets. Our customer base has a key advantage since our Foundries, Laboratories, Extrusion Mill, Shell Mouldings and CNC Machine shop are all located on a single site, which eliminates waste and allows excellent quality control at each stage. Our ability to reclaim swarf and machined chips allows us to offer competitive pricing for the parts that we either extrude or cast.

### Casting Range



📍 25 Grams to 10 Kgs

### Forging Sizes



📍 50 Grams to 6 Kgs

### Machining Sizes



📍 1 mm to 200 mm

### CONNECT WITH US Adinath Extrusion Pvt. Ltd.

📍 Plot No. 4051-4055,  
Bhagwan Mahavir Swami Marg,  
G.I.D.C., Phase-III, Dared,  
Jamnagar - 361004, Gujarat, India.

📞 +91 7600 55 9243 📞 +91 288 2730868  
✉ sales@adinathextrusion.com,  
marketing@adinathextrusion.com  
🌐 www.adinathextrusion.com

