



Adinath

Create, Enhance & Sustain

C-48200:NAVAL BRASS Specification Sheet

DESCRIPTION

C48200 Naval Brass is also known as Medium Leaded Brass because of the higher content of Lead as compared to other Naval Brass Alloys. The presence of Lead content is useful to produce Hot forging products which are easier to machine.



CHEMICAL COMPOSITION

Element	Cu	Fe	Zn	Pb	Sn	Oi
Min (%)	59.00	-	Balance	0.40	0.50	-
Max (%)	62.00	0.10		1.00	1.00	0.40

Note: Ni includes Co; Cu+ named elements >= 99.5%; Unless otherwise noted, single values represent maximums.

SHAPE



SOLID ROUND BARS

Size Range :
Dia 7 mm up to 120 mm.



SOLID HEX BARS

Size Range :
A/F 7 mm up to 100 mm.



SOLID SQUARE BARS

Size Range :
A/F 7 mm up to 90 mm.



SOLID RECTANGLE BARS

Size Range :
A/F 7 x 10 mm up to 100 x 50 mm.



HOLLOW BARS

Outer Diameter : In Round, Hex & Square.

Size Range : 30 mm up to 120 mm.

Inner Diameter : Round

Size Range : 20 mm up to 80 mm.



PROFILES & SECTIONS

As per Customers' Drawing



BAR LENGTH

Length : Up to 4 Meters

Delivery Condition : As Extruded or Cold Drawn.

STRAIGHT KNURLING



CROSS KNURLING



Straight Knurling & Cross Knurling will be available upon shape & size Feasibility of Brass Rod

C-48200:NAVAL BRASS



MECHANICAL PROPERTIES

Round (Dia)					
Range (mm)	UTS Min (MPA)	PS Min (MPA)	Elongation Min (%)	Hardness (HRB)	
3 to 12 Inclusive	415	185	18	-	
12 to 25 Inclusive	415	185	18	65-85	
25 to 50 Inclusive	400	180	20	60-85	
50 to 75 Inclusive	370	170	20	60-85	
Hex (A/F)					
Range (mm)	UTS Min (MPA)	PS Min (MPA)	Elongation Min (%)	Hardness (HRB)	
3 to 12 Inclusive	415	185	18	-	
12 to 25 Inclusive	415	185	18	65-85	
25 to 50 Inclusive	400	180	20	60-85	
50 to 70 Inclusive	370	170	20	60-85	
Square (A/F)					
Range (mm)	UTS Min (MPA)	PS Min (MPA)	Elongation Min (%)	Hardness (HRB)	
3 to 12 Inclusive	415	185	18	-	
12 to 25 Inclusive	415	185	18	65-85	
25 to 50 Inclusive	400	180	20	60-85	
50 to 60 Inclusive	370	170	20	60-85	
Rectangle					
Range (mm)	UTS Min (MPA)	PS Min (MPA)	Elongation Min (%)	Hardness (HRB)	
Thickness	3 to 12 Inclusive	415	185	18	-
	12 to 25 Inclusive	415	185	18	65-85
	25 to 50 Inclusive	400	180	20	60-85

PACKING



-  PVC Pipe Packing for Small Diameter Rods.
-  Hessian Cloth Packing.
-  Wooden Box Packing as per Customer requirements.

C-48200:NAVAL BRASS



FABRICATION PROPERTIES

Soldering	Brazing	Machinability Rating
Excellent	Excellent	50

TYPICAL USES

Product Category	Product
Marine	Hardware
Industrial	Gears, Screw Machine Parts, Products, Valve Stems.
Fasteners	Bolts, Fasteners.

VALUE ADDED SERVICES

AEPL manufactures and supplies Copper Alloys Extruded Bars to Domestic as well as International Markets. Our customer base has a key advantage since our Foundries, Laboratories, Extrusion Mill, Shell Mouldings and CNC Machine shop are all located on a single site, which eliminates waste and allows excellent quality control at each stage. Our ability to reclaim swarf and machined chips allows us to offer competitive pricing for the parts that we either extrude or cast.

Casting Range



 25 Grams to 10 Kgs

Forging Sizes



 50 Grams to 6 Kgs

Machining Sizes



 1 mm to 200 mm

CONNECT WITH US Adinath Extrusion Pvt. Ltd.

 Plot No. 4051-4055,
Bhagwan Mahavir Swami Marg,
G.I.D.C., Phase-III, Dared,
Jamnagar - 361004, Gujarat, India.

 +91 7600 55 9243  +91 288 2730868
 sales@adinathextrusion.com,
marketing@adinathextrusion.com
 www.adinathextrusion.com

